

**Setting Tool:**

Top Connection	3-1/2 IF	NC-38
Minimum ID	1.750in.	4,445cm
Maximum Tensile Capacity	250,000lbf	1112kN
Maximum Torque Capacity	11,500ft-lbf	15591N-m
Liner Release Pressure	750-2775psi	5,1-19,1MPa
Metal Forming Force	156,000lbf	694kN
Metal Forming Torque	1,100ft-lbf	1491N-m
Cement Plug Launch Pressure	335-2015psi	2,3-13,9MPa
Material Yield Strength	125ksi	861,8MPa

**Set Liner Top:**

Maximum Temperature	400°F	205°C
Maximum Hanging Weight	250,000lbs	113,4Mg
Polished Bore Receptacle ID	4.0in	102mm
Polished Bore Receptacle Length	72in	182,9cm
Differential Pressure	10,000psi	68,9MPa
Packer Elastomeric Material	Peroxide cured DuPont™ Viton® w/APA	
Hanger Body Metallic Material	Chrome-Nickle-Moly Steel Alloy	

**Assembly as deployed:**

Overall Tool Length	18.9ft	5,76m
Overall Tool Weight	1,000lbs	454kg
Maximum Tool OD	5.915in	15cm

**Seminole Services LLC**  
2002 Timberloch Pl. Suite 200  
The Woodlands, TX 77380  
281-296-5841 or 281-253-6181

*All Information presented is based on nominal dimensions and standard calculation methods. Seminole Services, LLC does not assume responsibility for results obtained from the use of this information as all installations are independent and unique. No warranty is expressed or implied.*